



MIXED REMOVABLE ALUMINIUM TIPPER

BODYWORK

- MAX. load capacity: 3 T
- Tipper platform in high quality aluminium sheet: 5083 H111 thickness 4 mm
- Longitudinal reinforcement spacers
- Sideboards in tubular aluminium profile, height 350 mm, thickness 2.8 mm, fold-down, removable, interchangeable right/left
- Closing of embedded sideboards
- Front face, height 450 mm, thickness 2.8 mm
- Cab Protect in galvanised steel, with grille (4.5 mm section), removable and without top cap
- Aluminium rear door, height 450 mm, thickness 2.8 mm, 2 leaves and bottom unhooking by manual unlocking
- Stops on sideboards and rear door
- Rear pillars in galvanised steel, thickness 3 mm, removable, with adjustable fixing bolt and conical fittings
- 2 rear rolls in aluminium fitted on self-lubricating ring (no greasing)

CRADLE

- Y-shaped frame rails, height 120 mm, thickness 8 mm
- Centre distance 850 or 1060
- Hook height 920 mm
- STEEL gripper axis diameter 30 welded on a steel pressed frame bolted to the structure
- Exterior and interior locking

SAFETY

- Anti-theft device to be locked


FINISH

- Shot blasting + 60 µm powder primer + 60 µm powder paint

MIXED REMOVABLE ALUMINIUM TIPPER

WEIGHT (in kg)

Weights are for information. Supplier thickness tolerances for steel or aluminium do not enable us to guarantee a weight within a tolerance of +/- 10%.



AND GUARANTEE OF UP TO 5 YEARS FOR YOUR BODYWORK

2-YEAR GUARANTEE

On purchasing your bodywork

3-YEAR GUARANTEE

3rd year free after registering your bodywork

5-YEAR GUARANTEE

JPM offers a 2-year guarantee extension